

**Battery powered strapping tool, for demanding plastic strapping applications****Characteristics**

Strapping qualities:	Polyester (PET) and Polypropylene (PP) plain and embossed
Strapping dimensions:	width 16.0 – 19.0 mm / 5/8 – 3/4" thickness 0.65 – 1.35 mm / .026 – .053"
Weight incl. battery:	4.3 kg / 9.6 lbs
Tool size with battery:	L351 x W134 x H143 mm / 13.8" x 5.3" x 5.6"
Type of seal:	Friction weld sealing
Average seal strength:	approx. 75% (dependent on strap quality)
Tension force:	500 – 4000 N / 112 – 900 lbs (adjustable)
Tension speed:	49 – 113 mm/s / 1.9 – 4.5 inch/s
Power supply:	Battery Li-Ion 18VDC / 5Ah
Suspension bracket:	Optional

**Advantages**

- High tension force up to 4.000N / 900 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single button) version available for efficient operation
- Brushless motor for less maintenance and improved life time
- Improved plates and guides – less effort to remove the tool from the strap
- No tension rocker – easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating
- Cycle counter included (special reader required)
- Battery, well protected
- Battery, charge indicator included
- Simple one-handed operation
- Tool is fully covered for finger protection
- Optional motor cooling fan available to reduce overheating risk

**Chart of types model P329**

Item no.	Model	Strap widths		Strap thicknesses		Max. tension		Tension speed	
		mm	inch	mm	inch	N	lbs	mm/sec	inch/sec
43.2522	P329/16/0.65-1.05	16	5/8	0,65-1,05	.026-.041	4.000	900	49-113	1.9-4.5
43.2532	P329/19/0.65-1.05	19	3/4	0,65-1,05	.026-.041	4.000	900	49-113	1.9-4.5
43.2533	P329/19/1.06-1.35	19	3/4	1,06-1,35	.042-.053	4.000	900	49-113	1.9-4.5
43.2722	P329/16/0.65-1.05/A	16	5/8	0,65-1,05	.026-.041	4.000	900	49-113	1.9-4.5
43.2732	P329/19/0.65-1.05/A	19	3/4	0,65-1,05	.026-.041	4.000	900	49-113	1.9-4.5
43.2733	P329/19/1.06-1.35/A	19	3/4	1,06-1,35	.042-.053	4.000	900	49-113	1.9-4.5

**A = Automatic model**
**Battery chargers for model P329**

Item no.	Model	Voltage / frequency	Countries
N5.4443	Li-Ion	220-240 V / 50-60 Hz	A, B, BG, BIH, BOL, BR, BY, CH, CL, CZ, D, DK, DZ, E, EAS, EST, ET, F, FIN, GE, GR, H, HK, HR, I, IL, IND, IR, IRQ, IS, JOR, KSA, KWT, L, LAR, LT, LV, MA, MC, MK, MOC, N, NL, P, PK, PE, PL, PRC, PY, RA, RCH, RI, RL, RO, ROK, ROU, RP, RUS, S, SK, SLO, SYR, THA, TN, TR, UA, UAE, YU, YV, (BRN), (BRU), (CY), (EAK), (EAT), (GB), (IRL), (M), (MAL), (OM), (SGP), (Y), (Z), (ZA), (ZW)
N5.4447	Li-Ion	120 V / 50-60 Hz	BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV
N5.4445	Li-Ion	220-240 V / 50-60 Hz	AUS, NZ

(..) = Adapter N52.2102 required

**Battery for model P329**

<u>Item no.</u>	<u>Battery</u>	<u>Voltage</u>	<u>Capacity</u>	<u>Charging time</u>
N5.4349	Li-Ion	18VDC	5Ah	approx. 80 min.

**Accessories**

P32.0223	Suspension bracket (pivoted)
P32.0231	Suspension bracket (fixed)
P32.0224	Wearing plate (metal) for rough and hard surfaces
P32.0225	Protection plate (metal) to protect complete bottom side
P32.0228	Motor cooling fan
P32.2061	Settings lock kit